

S39393

45W/LED/HID/5000K/100-277V/EX39 45 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP64 rated

- For outdoor & indoor use
- High-bay / Low-bay / Post-topEmits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60HzWorking Voltage AC90-305V

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
8 inch	8 inch	11 inch				

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39393

Item Number	Product Line	UPC	Input Voltage	' \/\/atte		Incandescent Equivalent	Fluorescent Equivalent		
S39393	Hi-Pro	045923303937	100 - 277	45	50/60Hz	300W	65W		

Equivalent	Base	Base	Lamp Code				Dimmable			Inches		nches	
175W	Mogul Extended	EX39	45W/LED/HID/5000K/100- 277V/EX39			Non-Dimmable Wh			White	8-13/16"	3-1	11/32"	
Initial Lumens	Average Rat Hours	ed	Kelvin Temp	Color	CR	l Bea	m Spr Deg	ead	Opera	ating Ten	nperature		Pack
6435	50000		5000	Natural Ligh	t 80		300 -2		-20C (-4F) to a maximum of +65C (+149F)			f	12
Package Type	CEC Status		DLC ID:	Material (RoH: Compl		UL or ETL Listed		UL Classification		Warranty	
Вох	Lawful for sale in California	L271RI	HFVSJW earch	Alumini	Aluminum Y		3	Yes		ULus - D ocation F	•	5 Year Limited	

Lamp Code



HID

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

ANSI

Base

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

Dimmable/Non-



MOL In

Finish

MOD In

@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051