

S39394

54W/LED/HID/5000K/100-277V/EX39 54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP64 rated

- For outdoor & indoor use
- High-bay / Low-bay / Post-top
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
8 inch	8 inch	15.75 inch				

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39394

Item	Product	UPC	Input		Operating	Incandescent	Fluorescent	
Number	Line		Voltage Watts		Frequency	Equivalent	Equivalent	
S39394	Hi-Pro	045923303944	100 - 277	54	50/60Hz	300W	85W	

	HID uivalent	Base	ANSI Base	Lamp Code		[Dimmable/Non- Dimmable			MOL In Inches	MOD In Inches	
2	250W	Mogul Extended	EX39	54W/LED/HID/5000K/100- 277V/EX39		ı	Non-Dimmable		White	9-1/32"	3-11/32"	
	nitial umens	Average Rated Hours	Kelvir Temp	Color	CRI	Beam Sp Dec		Burning Posit	ion	Оре	erating Ten	nperature
7	7722	50000	5000	Natural Light	80	300)	Up or Down Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pacl	k Packa K Typ	- CEC SI	atus	DLC ID:	Mat	erial	RoHS Complia	FII	UL	₋ Classi	fication	Warranty
12	Во	Υ	awful for sale LXDJHRLRK97 in California DLC Search		Alum	Aluminum Ye		Yes		ULus - I		5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051